

PRODUCT FEATURES


- Split doors and Upright series.
- Stainless steel interior and exterior.
- Programmable electronic controller and display. Standard with 8 x shelves.
- 2 years parts and labour warranty.
- Comes standard with 4 x lockable (115 mm) castors (not legs).



TECHNICAL DRAWING

POWER CORD 2300 LONG OUTSID

PRODUCT SPECIFICATION



20	Interior	Stainless Steel, ABS Plastic (Doors)
	Exterior	Stainless Steel, Galvanized Steel (Top,Rear,Bottom)
	Max Storage Capacity	1047L
	Temperature Control	Microprocessor adjustable from -23°C to -7°C
	Evaporator	Fin & Tube type
	Outside Dimensions	1200mm (W) x 800mm (D) x 2015mm(H)
	Inside Dimensions	1096mm (W) x 646mm (D) x 1484mm (H)
	Refrigeration System	Forced Air Circulation
	Weight Net/ Gross (kg)	149 / 180
	AC Supply Voltage	1 PHASE 220 - 240V 50Hz /10amp Plug
	Amperage	Rated: 4.9A Starting: 15.6A
	Refrigerant	R404A
	Operating Conditions	Ambient Temp.: 5-43°C Voltage Range: Rated Voltage ±6%

INSTALLATION REQUIREMENTS

- Equipment should not be located in direct sunlight or next to sources of high heat.*
- Allow at least 50 cm clearance between the front panel air inlet/outlet and the wall or other equipment for proper air circulation.*



For free 12 month extended warranty, register online within 4 weeks of purchase date. hoshizaki.com.au









^{*}Refer to manual for full installation & maintenance requirements.