


## Crescent 255ka Ice Maker - Modular


### **PRODUCT FEATURES**


- Individually shaped crescent ice.
- Protected by HoshiGuard Antimicrobial Agent.
- CycleSaver® technology includes a double-sided evaporator. uniquely crafted in stainless steel, which produces ice on both sides, resulting in more ice in less amount of time.
- EverCheck Control board with audible alarm and diagnostic features, designed to assist services technicians in diagnosing problems.
- Durable stainless-steel exterior
- Easily removable & cleanable air filters on front panel.
- Ice storage bin, top kit and water filter sold separately.


#### TECHNICAL DRAWING













For free 6 month extended warranty, register online within 4 weeks of purchase date. hoshizaki.com.au













## PRODUCT SPECIFICATION

Production Capacity / 24hrs	Approx. 255kg @ 21°C Air temp; 15°C Water Approx. 221kg @ 32°C Air temp; 21°C Water
Recommended Storage Bins	B-301 SA   B-501 SA   B-801 SA   B-1300 SS   B- 1500 SS
Freeze Cycle Time	Approx. 26.8 Min (At. 21°C Air ; 15°C Water)
Ice Production / cycle	Approx. 5.3kg / 572pcs
Dimensions	560mm (W) x 625mm (D) x 610mm (H)
Cooling	Air
Weight Net/Gross (kg)	57/73
Refrigeration System	Forced Air Circulation
AC Supply Voltage	1 PHASE 220-240V 50Hz
Amperage	Running: 4.9A Starting: 24A
Refrigerant Charge	R404A/780g
Operating Conditions:	
Ambient Temp	7-40°C
Water Supply Temp	7-35°C
Water Supply Pressure	0.07-0.8MPa (0.7-8bar)
Voltage Range	±6%
Electrical consumption	984W (AT. 32°C; WT 21°C)
Water Consumption / 24hrs	Approx. 0.55m³/d(AT. 21°C; WT 15°C)

# **INSTALLATION REQUIREMENTS**

- Qualified plumber required for installation.
- Included accessories & fittings pack can be found behind front panel.
- Allow 30cm clearance at rear, sides and top for proper air circulation and ease of maintenance.
- Install bin control switch according to installation manual.
- Hoshizaki recommends the use of a compatible water filter to prevent non-warrantable scale & sediment complications

<sup>\*</sup>Refer to manual for full installation & maintenance requirements.