



ITEM	Hoshizaki Undercounter Refrigerator
MODEL	RTE-170SDA-GN-ML
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.43kVA(1.9A)
AMPERAGE	Rated 1.4A
ELECTRIC CONSUMPTION	Motor 195W(Power Factor65%) Heater 202W Refrigeration 242W Defrost 209W
HEAT REJECTION	*W
POWER CORD	2.3m (AU Plug with Earth Wire)
EFFECTIVE CAPACITY	412L
OUTSIDE DIMENSIONS	1660mm (W) x 700mm (D) x 815mm (H)
INSIDE DIMENSIONS	1290mm (W) x 527mm (D) x 588mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom)
INTERIOR	Stainless Steel, ABS Plastic
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
DOOR	Full Stainless Steel Doors External And Interior
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Glass Tube Heater
COMPRESSOR	Hermetic 110W
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R134a
TEMPERATURE CONTROL	Microprocessor controlled Adjustable from -6 to 12° C
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
COMPRESSOR PROTECTION	Motor Protector
CASTER	Urethane (76mm DIA, 115mm HIGH)
SHELF	6pcs.
WEIGHT	Net: 103kg (Gross: Approx. *kg)
PACKAGE	Carton(Woody Base) 1725mm (W) x 780mm (D) x 990mm (H)
ACCESSORIES	Shelf Clip x 20, Support Shelf x 2
OPERATING CONDITIONS	Ambient Temperature: 5-43° C Voltage Range: Rated Voltage±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow, pipe connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 43° C and power supply of 230V 50Hz. The amperage and electric consumption are based on measurements at ambient temperature of 43° C and power supply of 230V 50Hz.
3. The cabinet temperature range of -6 to 12° C is guaranteed at ambient temperature of 30° C.
4. Product code: T040-D009 (For HL)

*Customized specifications
Caster with stopper H=115mm
Power Cord Australian 3 Pin Plug
ML Door

HOSHIZAKI UNDERCOUNTER REFRIGERATOR RTE-170SDA-GN-ML (FOR HL)

APPROVED KAWAKAMI	CHECKED WANG	DESIGNED LIANG	DRAWN KAWAKAMI	SCALE 1/30	TRIGONOMETRY
NAGASE APPROVED	SHAN DESIGNED	DATE 2019.12.03	DATE 2018.08.03	DRAWING NO. D23392	SYMBOL ⚠